

SikaTite® Non-Porous Primer

Universal, solvent free, acrylic based primer

Description	Single component primer for application on both porous and non-porous substrates in preparation for use with SikaTite® membrane systems.
Uses	■ Priming of interior substrates and screeds
Advantages	■ Rapid cure time ■ Reduces pin-holing ■ Good adhesion to both porous and non-porous substrates ■ Easy to apply ■ Low consumption rate ■ Low VOC
Storage and Shelf Life	12 months when stored in cool, dry and > 5°C
Instructions for Use	
Surface Preparation	<ul style="list-style-type: none">• Substrates should be structurally sound and not subject to rising moisture• All dust, residues which reduce adhesion should be removed• Any loose, friable material should be removed and the substrate repaired using appropriate Sika repair material• Gypsum based substrates should be ground and vacuumed prior to application of SikaTite® Non-Porous Primer
Mixing	Product should be thoroughly shaken, or stirred prior to use. For normal absorbent, porous substrates, dilute 1 part primer : 3 parts water For non-porous substrates, old residue which can't be removed, product is ready to use and should not be diluted.
Application	Product should be evenly applied using a medium nap roller (~12mm), brush, or spray to a clean substrate. Puddling should be avoided.
Consumption Rate	50 – 80ml / m ²
Drying Time	Porous substrates ~ 10 minutes Non-Porous substrates ~ 30 minutes Wooden substrates ~ 2 hours Note: all time are based upon ambient temperature of 23°C and are subject to climatic variation Subsequent works can commence after this time
Cleaning	Tools should be cleaned with water immediately after use



Technical and Physical Data

Form Water based acrylic

Application Temperature (ambient & substrate) +5°C - +35°C

Substrate Moisture Content 4%

Packaging 1 & 5 litre

Important Notes

- Cure times are susceptible to change based upon atmospheric conditions

Handling Precautions

- Avoid contact with skin and eyes.
- Wear protective gloves and eye protection during work.
- If skin contact occurs, wash skin thoroughly.
- If in eyes, hold eyes open, flood with warm water and seek medical attention without delay.
- Avoid contact with foodstuffs and utensils.
- A full Safety Data Sheet is available from Sika on request.

Important Notification The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.



Sika Australia Pty Limited
ABN 12 001 342 329

aus.sika.com
Tel: 1300 22 33 48