



# X230 DENSI-PROOF REPELLER™

Technical  
Data  
Sheet

Issued: 9th June 2015  
Document #: TDS 106 v4f  
Page 1 of 2



## INTERNAL AND EXTERNAL PROTECTION FOR CONCRETE

### Description & Uses

X230 Densi-Proof™ Repeller is a single pack one application spray on system that deeply penetrates new or existing concrete, provides curing, permanent waterproofing and protection. The added X300 Repeller provides surface protection and ease of cleaning against acids, oils, water based stains, chemicals, body fluids, wine, grease and others.

### Features and Benefits

- Will cure concrete equal to water pond curing.
- Permanently waterproofs concrete from any direction.
- Makes concrete impermeable, increasing longevity.
- Resists surface staining.
- Increases tensile & compressive strength.
- Resists freeze thaw damage.
- Retards efflorescence.
- Stabilises pH.
- Used on horizontal substrates.
- Zero VOC, environmentally friendly, user safe.
- Compatible with epoxy and acrylic line marking paints.
- Eliminates moulds and odours.
- Indefinite shelf life.
- Minimum site disruption, trafficable after 2 hours.
- Reduces dry shrinkage cracking.

### Physical and Chemical Properties

<b>Appearance:</b>	Low viscosity cloudy-white liquid.	<b>Relative Density:</b>	Ca. 1.10 @ 20°C.
<b>Odour:</b>	Almost none.	<b>Solubility:</b>	Fully miscible in water.
<b>pH:</b>	Ca. 11.4	<b>Auto-ignition Temperature:</b>	Product is not self-igniting.
<b>Initial Boiling Point/ Boiling Range:</b>	> 100°C @ 760 mm Hg.	<b>Viscosity:</b>	Low.
<b>Flash-point:</b>	Not applicable.	<b>Volatile Organic Compounds (VOC) Content;</b>	0.0 % w/w.
<b>Flammability (solid, gas):</b>	Not applicable.	<b>Per Cent Volatile:</b>	Ca. 0 % w/w.
<b>Upper/Lower Flammability or Explosive Limits:</b>	Not applicable.		

### Recommended Substrate Conditions & Preparation

<b>Freshly Placed Concrete:</b>	5m <sup>2</sup> per litre.	periods.
<b>Existing Concrete:</b>	5m <sup>2</sup> per litre	

#### Important Notes:

1. Wax, paint, curing compounds or a burnished surface restricting access to concrete's interior must be chemically or mechanically removed for X230 Densi-Proof™ Repeller to penetrate and work properly.
2. Areas of high porosity have a faster penetration rate. These areas appear dry immediately after spraying and will require additional product.
3. Do not apply on frozen substrate or when temperature is below 3°C when getting colder. Call for advice if applying during colder periods.
4. Do NOT apply if rain is forecast within 3 hours.
5. Before applying any paint, wait 24 hours after application with X230 Densi-Proof™ Repeller. Always follow paint manufactures surface preparation guidelines and requirements.
6. X230 Densi-Proof™ Repeller may etch glass/tiles or dull brushed and shiny aluminium and can be difficult to remove from other surfaces once it dries. Cover and mask surrounding surfaces or rinse immediately if sprayed.
7. We recommend the use of a painters mask during application. Refer to MSDS available from [www.oxtekaus.com](http://www.oxtekaus.com)



# X230 DENSI-PROOF REPELLER™

## Technical Data Sheet

### Application Guide

Issued: 9th June 2015  
Document #: TDS 106 v4f  
Page 2 of 2

#### On Already-Set Concrete:

Note: In hot climates, mist-wet the surface with water and remove any puddles prior to application.

Apply X230 Densi-Proof™ Repeller using a pump pack or low pressure airless spray unit, complete with fan spray nozzle. Holding spray tip (eg .019" - .024") 150mm from surface, apply X230 Densi-Proof™ Repeller at minimum rate of 5m<sup>2</sup> per litre with an overlapping spray pattern of 50%. Begin application at the lowest elevation. For example, walls and slopes should be applied side to side, from the bottom up.

Using a soft broom sweep and spread out puddled product as it penetrates. Do not allow product to puddle dry on the surface. If product gels on the surface remove with a squeegee.

#### As a Cure Method at Time of Pour:

Apply with a low-pressure non-atomizing, spray apparatus such as a pump-tank sprayer or airless set at 800psi. X230 Densi-Proof™

Repeller is ideally applied to the newly-poured concrete surface as soon as is practical following its surface finishing phase. Should conditions require the surface to be walked on, for application, concrete should be allowed the time to adequately set, so as not to imprint or mar its surface during application. Recommended minimum coverage rate as a cure method is 5m<sup>2</sup> per litre.

#### Caution: For newly placed unused concrete only.

For existing, soiled, used and old concrete a two part system must be used. X200 Densi-Proof™ will decontaminate and purge deep seated unwanted substances to the surface and these need to be removed prior to finishing with the X300 Repeller. Use a two part system of X200 Densi-Proof™ or X220 Moisture-Fix (refer to TDS) and then clean and apply X300 Repeller. Call your Oxtek Rep for advice.

### Additional Data and Precautions

Available in 15, 200 and 1200 litre containers.

1. Any coatings that may restrict access to the concrete's interior must be chemically or mechanically removed for X230 Densi-Proof™ Repeller to penetrate.
2. Protect areas not intended for coverage.
3. X230 Densi-Proof™ Repeller may etch glass/tiles or dull shiny aluminium and can be difficult to remove from other surfaces once it dries.

4. Do not apply on frozen substrate or when temperature is below 3°C when getting colder. Call for advice if applying during colder periods.

5. X230 Densi-Proof™ Repeller's spray mist is not hazardous to breathe. However, we do recommend the use of a face mask during application. Refer to MSDS.

6. For more information read Material Safety Data Sheet available at [www.oxtekaus.com](http://www.oxtekaus.com)

### Testing and Certifications



Test		Control Sample*	Densi Proof Sample	Results Comparison
Designation	Property			
AS 1012.9 ASTM C39	Compressive Strength	28.9 MPa 4,191 psi	31.0 MPa 4,496 psi	7% Increase
AS 1012.8 ASTM C78	Flexural Strength	2.52 MPa 365 psi	2.89 MPa 419 psi	15% Increase
Chaplin Abrader	Abrasion Loss	2.47 mm 0.10 in	1.46 mm 0.06 in	41% Reduction
Surface Dusting		2.57 g/0.25 m <sup>2</sup>	1.78 g/0.25 m <sup>2</sup>	31% Reduction
ASTM C1202	Rapid Chloride Penetration	597 / 543 / 10,097 Coulombs	148 / 136 / 6,582 Coulombs	35% to 75% Reduction
HKHA B2.9	Sorptivity	0.164 mm/(min) <sup>1/2</sup>	0.010 mm/(min) <sup>1/2</sup>	94% Reduction
ACCI Water Permeability Test	Water Permeability	1.5 x 10 <sup>-13</sup> m/s	2.5 x 10 <sup>-14</sup> m/s	83% Reduction
USACOE C48	Water Permeability	NA	0 Leakage @ 30.5 m Head Pressure 0 Leakage @ 100 ft Head Pressure	
DIN 1048	Water Permeability	98.4 mm @ 0.33 hrs 3.9 in @ 0.33 hrs	5.5 mm @ 72 hrs 0.22 in @ 72 hrs	94% Reduction
ASTM C666	Mass Loss @ 300 Freeze/Thaw Cycles	4.8%	0.7%	85% Reduction

\*Note – All control samples were moisture cured.

March 2013

